

EXPRESS MAIL NO. EL 920 880 250 US

DATE OF MAILING 12/20/01

Our Case No. 9281-4256
Client Reference No. FC US00053

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
Hidetaka Numata et al.)
Serial No. To Be Assigned)
Filing Date: Herewith)
For: Manual Input Device Which Provides its)
Control Knob With Plural Modes of)
Operation Feeling, and Car-Mounted)
Apparatus Controller Based Thereon)

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Prior to examination of the above-identified application, please amend the application as follows:

In the Drawings

Please replace Figs. 8-11 with the corrected Figs. 8-11 enclosed herewith. The corrections to the figures have been marked in red. Applicants respectfully request that the Examiner approve the corrections. Applicants will submit corrected formal drawings upon receiving a Notice of Allowance.

In the Specification

Please rewrite the paragraph on page 15, lines 6-7 as follows:
(Amended) Figs. 17A and 17B show the configuration of a conventional manual input device.

In the Claims

Please rewrite Claim 1 as follows:

1. (Amended) A manual input device comprising:
 - a knob;
 - a feeling providing device which has at least two kinds of feeling patterns; and
 - an actuator which activates the feeling providing device and changes an operation feeling given to the knob.

Please rewrite Claim 5 as follows:

5. (Amended) The manual input device according to Claim 1,
 - wherein the feeling providing device comprises one of a disc and cylinder which bears plural feeling patterns (rows) and is fixed to a control shaft to be manipulated by the knob; and one of a ball and pin elastically forced to contact the one of the disc and cylinder, and
 - wherein the actuator linearly reciprocates the one of the ball and pin in a direction where the plural feeling patterns are arranged.

Please rewrite Claim 6 as follows:

6. (Amended) The manual input device according to Claim 1,
 - wherein the feeling providing device comprises one of a disc and cylinder which has a single feeling pattern (row) and is fixed to a control shaft to be manipulated by the knob; and one of plural balls and pins elastically forced to contact the one of the disc and cylinder, and
 - wherein the actuator linearly reciprocates a selected one of the one of the plural balls and pins in a direction where the selected one of the one of the plural balls and pins selectively engages with the feeling pattern.

Please rewrite Claim 7 as follows:

7. (Amended) The manual input device according to Claim 1,
 - wherein the feeling providing device comprises a rotary polyhedron which bears plural feeling patterns (rows) arranged in parallel along an axial direction of an outer surface, and

wherein the actuator reciprocally rotates the rotary polyhedron around an axis of the rotary polyhedron, with one end of a control shaft to be manipulated by the knob being in contact with the outer surface of the rotary polyhedron bearing the feeling patterns.

Please rewrite Claim 8 as follows:

8. (Amended) A manual input device comprising:

a knob;

feeling providing device which provides the knob with an operation feeling;

an actuator which activates the feeling providing device;

a detector which detects an operating condition of the knob; and

an input/output section which exchanges signals with an external device controlled by the knob,

wherein the actuator is controlled according to a control signal generated based on an external signal from an external detector connected at least with the external device.

Please rewrite Claim 12 as follows:

12. (Amended) The manual input device according to Claim 8,

wherein the feeling providing device comprises one of a disc and cylinder which bears plural feeling patterns (rows) and is fixed to a control shaft to be manipulated by the knob; and one of a ball and pin elastically forced to contact the one of the disc and cylinder, and

wherein the actuator linearly reciprocates the one of the ball and pin in a direction where the plural feeling patterns are arranged.

Please rewrite Claim 13 as follows:

13. (Amended) The manual input device according to Claim 8,

wherein the feeling providing device comprises one of a disc and cylinder which bears a single feeling pattern (row) and is fixed to a control shaft to be manipulated by the knob; and one of plural balls and pins elastically forced to contact the one of the disc and cylinder, and

wherein the actuator linearly reciprocates a selected one of the one of the plural balls and pins in a direction where the selected one of the one of the plural balls and pins selectively engages with the feeling pattern.

Please rewrite Claim 14 as follows:

14. (Amended) The manual input device according to Claim 8,
wherein the feeling providing device comprises a rotary polyhedron which bears plural feeling patterns (rows) arranged in parallel along an axial direction of an outer surface, and
wherein the actuator reciprocally rotates the rotary polyhedron around an axis of the rotary polyhedron, with one end of a control shaft to be manipulated by the knob being in contact with the outer surface of the rotary polyhedron bearing the feeling patterns.

Please rewrite Claim 15 as follows:

15. (Amended) A manual input device comprising:
a knob;
a feeling providing device which provides the knob with an operation feeling;
an actuator which activates the feeling providing device;
a control section for the actuator;
a detector which detects an operating condition of the knob; and
an input/output section which exchanges signals with an external device controlled by the knob,
wherein an external signal from an external detector connected at least with the external device is inputted into the control section through the input/output section to generate a control signal for the actuator to match at least the external signal, and wherein the actuator is controlled according to the control signal.

Please rewrite Claim 16 as follows:

16. (Amended) A manual input device comprising:
a knob;
a feeling providing device which provides the knob with an operation feeling;
an actuator which activates the feeling providing device;

a control section for the actuator;
a detector which detects an operating condition of the knob; and
an input/output section which exchanges signals with an external device controlled by the knob,

wherein both a detection signal at least from the detector and an external signal from an external detector connected with the external device are inputted into the external device to generate control information for the actuator to match the detection signal and the external signal, wherein the control information is picked up by the control section through the input/output section to generate a control signal for the actuator to match the control information, and wherein the actuator is controlled according to the control signal.

Please rewrite Claim 17 as follows:

17. (Amended) A manual input device comprising:

a knob;
a feeling providing device which provides the knob with an operation feeling;
an actuator which activates the feeling providing device;
a detector which detects an operating condition of the knob; and
an input/output section which exchanges signals with an external device controlled by the knob,

wherein both a detection signal at least from the detector and an external signal from an external detector connected with the external device are inputted into the external device to generate a control signal for the actuator to match the detection signal and the external signal, and wherein the actuator is controlled according to the control signal.

Please rewrite Claim 18 as follows:

18. (Amended) A car-mounted apparatus controller comprising:

a function selection switch to select one function among various functions to be controlled; and
a manual input device to control the function selected by the function selection switch,
the manual input device comprising:

a knob;
a feeling providing device having at least two kinds of feeling patterns;
and
an actuator to activate the feeling providing device and changing an operation feeling given to the knob.

Please rewrite Claim 19 as follows:

19. (Amended) A car-mounted apparatus controller comprising:
an electric apparatus selection switch to select an electric apparatus to be controlled;
a function selection switch to select one of various functions of the electric apparatus selected by the apparatus selection switch; and
a manual input device to control a function selected by the function selection switch,
the manual input device comprising:
a knob;
a feeling providing device to provide the knob with an operation feeling;
an actuator to activate the feeling providing device;
a detector to detect an operating condition of the knob; and
an input/output section which exchanges signals with an external device controlled by the knob,
wherein the actuator is controlled according to a control signal generated based on both a detection signal at least from the detector and an external signal from an external detector connected with the external device.

In the Abstract of the Disclosure

Please rewrite the Abstract of the Disclosure as follows:

(Amended) ABSTRACT OF THE DISCLOSURE


A changeable operation feeling (tactile sensation) is provided for a user manipulating the knob of manual input device. The manual input device includes a feeling providing device which has plural discs fixed to a control shaft, bearing feeling patterns on their circumferential surfaces and a ball holder which works in conjunction with the discs to provide an operation feeling to the knob. An actuator is driven to move up or down the ball holder to select the feeling pattern to be

elastically forced to contact the ball to change an operation feeling as the user rotates the knob. A car-mounted apparatus controller incorporates this type of manual input device for functional control of car-mounted electric apparatuses.

REMARKS

Applicants have rewritten portions of the specification, Claims 1, 5-8 and 12-19 and the Abstract of the Disclosure. The changes from the previous version to the rewritten version are shown in attached Appendix A, with strikethrough for deleted matter and underlines for added matter.

Respectfully submitted,



Gustavo Siller, Jr.
Registration No. 32,305
Attorney for Applicants

BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(312) 321-4200

APPENDIX A
Attorney Docket No. 9281-4256
Manual Input Device Which Provides its Control Knob With Plural Modes
of Operation Feeling, and Car-Mounted Apparatus Controller
Based Thereon
Hidetaka Numata et al.

In the Specification

Please amend the paragraph on page 15, lines 6-7 as follows:

(Amended) Figs. 17A and 17B shows the configuration of a conventional manual input device.

In the Claims

Please amend Claim 1 as follows:

1. (Amended) A manual input device comprising:

a knob;

a feeling providing ~~means~~device which ~~have~~has at least two kinds of feeling patterns; and

an actuator which activates the feeling providing ~~means~~device and changes an operation feeling given to the knob.

Please amend Claim 5 as follows:

5. (Amended) The manual input device according to Claim 1,

wherein the feeling providing ~~means~~device comprises one of a disc ~~or~~and cylinder which bears plural feeling patterns (rows) and is fixed to a control shaft to be manipulated by the knob; and one of a ball ~~or~~and pin elastically forced to contact the one of the disc ~~or~~and cylinder, and

wherein the actuator linearly reciprocates the one of the ball ~~or~~and pin in a direction where the plural feeling patterns are arranged.

Please amend Claim 6 as follows:

6. (Amended) The manual input device according to Claim 1,

wherein the feeling providing ~~means~~device comprises one of a disc ~~or~~and cylinder which has a single feeling pattern (row) and is fixed to a control shaft to be manipulated by the knob; and one of plural balls ~~or~~and pins elastically forced to contact the one of the disc ~~or~~and cylinder, and

wherein the actuator linearly reciprocates a selected one of the one of the plural balls or and pins in a direction where ~~it~~ the selected one of the one of the plural balls and pins selectively engages with the feeling pattern.

Please amend Claim 7 as follows:

7. (Amended) The manual input device according to Claim 1,
wherein the feeling providing ~~means~~device comprises a rotary polyhedron which bears plural feeling patterns (rows) arranged in parallel along an axial direction of ~~its~~an outer surface, and
wherein the actuator reciprocally rotates the rotary polyhedron around ~~its~~an axis of the rotary polyhedron, with one end of a control shaft to be manipulated by the knob being in contact with the outer surface of the rotary polyhedron bearing the feeling patterns.

Please amend Claim 8 as follows:

8. (Amended) A manual input device comprising:
a knob;
feeling providing ~~means~~device which provides the knob with an operation feeling;
an actuator which activates the feeling providing ~~means~~device;
~~detecting means~~a detector which detects an operating condition of the knob; and
an input/output section which exchanges signals with an external device controlled by the knob,
wherein the actuator is controlled according to a control signal generated based on an external signal from ~~an external detecting means~~detector connected at least with the external device.

Please amend Claim 12 as follows:

12. (Amended) The manual input device according to Claim 8,
wherein the feeling providing ~~means~~device comprises one of a disc ~~or and~~ cylinder which bears plural feeling patterns (rows) and is fixed to a control shaft to be manipulated by the knob; and one of a ball ~~or and~~ pin elastically forced to contact the one of the disc ~~or and~~ cylinder, and

wherein the actuator linearly reciprocates the one of the ball ~~or~~ and pin in a direction where the plural feeling patterns are arranged.

Please amend Claim 13 as follows:

13. (Amended) The manual input device according to Claim 8,
wherein the feeling providing meansdevice comprises one of a disc
or and cylinder which bears a single feeling pattern (row) and is fixed to a control
shaft to be manipulated by the knob; and one of plural balls ~~or~~ and pins elastically
forced to contact the one of the disc ~~or~~ and cylinder, and
wherein the actuator linearly reciprocates a selected one of the one of
the plural balls ~~or~~ and pins in a direction where itthe selected one of the one of the
plural balls and pins selectively engages with the feeling pattern.

Please amend Claim 14 as follows:

14. (Amended) The manual input device according to Claim 8,
wherein the feeling providing meansdevice comprises a rotary
polyhedron which bears plural feeling patterns (rows) arranged in parallel along an
axial direction of itsan outer surface, and
wherein the actuator reciprocally rotates the rotary polyhedron around
itsan axis of the rotary polyhedron, with one end of a control shaft to be manipulated
by the knob being in contact with the outer surface of the rotary polyhedron bearing
the feeling patterns.

Please amend Claim 15 as follows:

15. (Amended) A manual input device comprising:
a knob;
a feeling providing meansdevice which provides the knob with an
operation feeling;
an actuator which activates the feeling providing meansdevice;
a control section for the actuator;
detecting meansa detector which detects an operating condition of the
knob; and
an input/output section which exchanges signals with an external
device controlled by the knob,

wherein an external signal from ~~an external detecting means~~detector connected at least with the external device is inputted into the control section through the input/output section to generate a control signal for the actuator to match at least the external signal, and wherein the actuator is controlled according to the control signal.

Please amend Claim 16 as follows:

16. (Amended) A manual input device comprising:

a knob;

a feeling providing means~~device~~ which provides the knob with an operation feeling;

an actuator which activates the feeling providing ~~means~~device;

a control section for the actuator;

~~detecting means~~a detector which detects an operating condition of the knob; and

an input/output section which exchanges signals with an external device controlled by the knob,

wherein both a detection signal at least from the ~~detecting means~~detector and an external signal from ~~an external detection means~~detector connected with the external device are inputted into the external device to generate control information for the actuator to match the detection signal and the external signal, wherein the control information is picked up by the control section through the input/output section to generate a control signal for the actuator to match the control information, and wherein the actuator is controlled according to the control signal.

Please amend Claim 17 as follows:

17. (Amended) A manual input device comprising:

a knob;

a feeling providing means~~device~~ which provides the knob with an operation feeling;

an actuator which activates the feeling providing ~~means~~device;

~~detecting means~~a detector which detects an operating condition of the knob; and

an input/output section which exchanges signals with an external device controlled by the knob,

wherein both a detection signal at least from the ~~detecting means~~detector and an external signal from ~~an external detection means~~detector connected with the external device are inputted into the external device to generate a control signal for the actuator to match the detection signal and the external signal, and wherein the actuator is controlled according to the control signal.

Please amend Claim 18 as follows:

18. (Amended) A car-mounted apparatus controller comprising:

a function selection switch ~~for selecting~~to select one function among various functions to be controlled; and

a manual input device ~~for~~to controlling the function selected by the function selection switch,

the manual input device comprising:

a knob;

a feeling providing means~~device~~ having at least two kinds of feeling patterns; and

an actuator ~~for~~to ~~activating~~activate the feeling providing ~~means~~device and changing an operation feeling given to the knob.

Please amend Claim 19 as follows:

19. (Amended) A car-mounted apparatus controller comprising:

an electric apparatus selection switch ~~for~~to selecting an electric apparatus to be controlled;

a function selection switch ~~for selecting~~to select one of various functions of the electric apparatus selected by the apparatus selection switch; and

a manual input device ~~for controlling~~to control a function selected by the function selection switch,

the manual input device comprising:

a knob;

a feeling providing means~~for providing~~device to provide the knob with an operation feeling;

an actuator ~~for activating~~to activate the feeling providing ~~means~~device;

~~detecting means for detecting a detector to detect an operating~~
condition of the knob; and

an input/output section which exchanges signals with an external
device controlled by the knob,

wherein the actuator is controlled according to a control signal
generated based on both a detection signal at least from the ~~detecting~~
~~means detector~~ and an external signal from ~~an external detecting means detector~~
connected with the external device.

In the Abstract of the Disclosure

Please amend the Abstract of the Disclosure as follows:

(Amended) ABSTRACT OF THE DISCLOSURE

This invention provides a manual input device by which the ~~A changeable~~
operation feeling (tactile sensation) ~~is provided to the~~ for a user manipulating it ~~the~~
knob ~~of manual input device can be changed as appropriate, and also a car-mounted~~
~~apparatus controller which uses this type of manual input device. A~~ The manual input
device comprises: a housing; a control shaft which is rotatably supported by the
housing; a knob fixed to one end of the control shaft; and feeling providing means,
actuator and first and second position sensors which are all housed in the housing.
~~The~~ includes a feeling providing means ~~comprises: device which has~~ plural discs
fixed to the a control shaft, bearing first to third feeling patterns on their
circumferential surfaces; and a ball holder which works in conjunction with the discs
to provide an operation feeling to the knob. ~~The~~ An actuator is driven to move up or
down the ball holder to select the feeling pattern to be elastically forced to contact
the ball to change an operation feeling as the user rotates the knob. ~~The~~ A car-
mounted apparatus controller incorporates this type of manual input device as
~~means for functional control of car-mounted electric apparatuses.~~

FIG. 8




FIG. 9




FIG. 10




FIG. 11

